



Corrugated Stainless Steel Flexible
 Connectors for GE Autotrol bypass
 Specification Sheet

SPECIFICATION:

Furnish and install Corrugated Stainless Steel Connector for GE Autotrol bypass

DESIGN FEATURES: Mega-flow SUPER Water-flex™

- 304 Series Stainless Steel
- Easy Installation
- Installs to GE Autotrol Bypass
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chromed brass nut
- Dupont Zytel Nylon Nut
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- High Temp EPDM Washer
- Chlorine and Chloramine Resistant
- Resists work hardening
- Burst pressure approx 1850 psi
- 100% Leak Tested
- Working pressure 200 psi
- No Sweat Installation
- Lifetime Warrantee
- Temperature rating 40 – 250 degrees F
- Bright annealed

COMPLIANCES/LISTINGS:

- * ICC-ES PMG
- * ICC Listed, Tested & Certified
- * UPC, IPC, IMC, IRC (USA)
- * Low Lead Compliant California H & S Code 116875
- * ASME A112.18.6/CSA B125.6-2009 Compliant
- * NSF-61 (ICC-ES PMG Certified to ANSI/NSF section 9)

<u>Model #</u>	<u>Description</u>	<u>Length</u>
SWCN13434	1 3/4"-12UN Nylon x 3/4" FIP	12",18"
SWCN1341	1 3/4"- 12UN Nylon x 1" FIP	12",18"



Product Submittal

Job Name: _____

Date: _____

Model# _____ Quantity: _____

 Architect/Contractor:

