



Corrugated Stainless Steel Flexible Water Heater/ Softener Connectors Specification Sheet

SPECIFICATION:

Furnish and install Corrugated Stainless Steel Water Heater/Softener Connector

DESIGN FEATURES: Mega-flow SUPER Water-flex™

- 304 Series Stainless Steel
- Approximately .63" I.D.
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chrome plated brass nut
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- High Temp EPDM Washer
- Chlorine and Chloramine Resistant
- Resists work hardening
- Burst pressure approx 1850 psi
- 100% Leak Tested
- Working pressure 200 psi
- No Sweat Installation
- Lifetime Warrantee
- Temperature rating -40 to 220 degrees F
- Bright annealed

COMPLIANCES/LISTINGS:

- * ICC-ES PMG
- * ICC Listed, Tested & Certified
- * UPC, IPC, IMC, IRC (USA)
- * Low Lead Compliant California Health & Safety Code 116875
- * ASME A112.18.6/CSA B125.6-2009 Compliant
- * NSF-61 (ICC-ES PMG Certified to ANSI/NSF section 9)

Model #	Description	Length
GFF030412	3/4" FIP x 3/4" FIP	12"
GFF030415	3/4" FIP x 3/4" FIP	15"
GFF030418	3/4" FIP x 3/4" FIP	18"
GFF030424	3/4" FIP x 3/4" FIP	24"

3/4" O.D. with .63" I.D. SS Tube



Product Submittal

Job Name: _____
 Date: _____
 Model# _____ Quantity: _____

 Architect/Contractor: _____

ANSI/NSF 61



Compliant to AB1953

ASME A112.18.6