



**Corrugated Stainless Steel Flexible  
Boiler/Water Softener Connectors  
Specification Sheet**

**SPECIFICATION:**

Furnish and install Corrugated Stainless Steel Boiler or Softener Connector

**DESIGN FEATURES: Mega-flow SUPER Water-flex™**

- 304 Series Stainless Steel
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chrome plated brass nut
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- High Temp EPDM Washer  
Chlorine and Chloramine Resistant
- Resists work hardening
- Burst pressure approx 1850 psi
- 100% Leak Tested
- Working pressure 200 psi
- No Sweat Installation
- Lifetime Warrantee
- Temperature rating -40 to 220 degrees F
- Bright annealed

**COMPLIANCES/LISTINGS:**

- \* ICC-ES PMG
- \* ICC Listed, Tested & Certified
- \* UPC, IPC, IMC, IRC (USA)
- \* Low Lead Compliant California H & S Code 116875
- \* ASME A112.18.6/CSA B125.6-2009 Compliant
- \* NSF-61 (ICC-ES PMG Certified to ANSI/NSF section 9)

<u>Model #</u>	<u>Description</u>	<u>Length</u>
SWC-2 x 18	2" FIP x 2" FIP	18"
SWC-2 x 24	2" FIP x 2" FIP	24"



<b>Product Submittal</b>	
Job Name: _____	
Date: _____	
Model# _____	Quantity: _____
Architect/Contractor: _____	
_____	

