



**Corrugated Stainless Steel Flexible
 Water Softener Connectors for
 Culligan & Erie Bypasses
 Specification Sheet**

SPECIFICATION:

Furnish and install Corrugated Stainless Steel Softener Connector for **Culligan & Erie** Bypasses only!

DESIGN FEATURES: Mega-flow SUPER Water-flex™

- 304 Series Stainless Steel
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chrome plated brass nut
- Dupont Zytrel “Black Nylon” Nut
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- High Temp EPDM Washer
- Chlorine and Chloramine Resistant
- Resists work hardening
- Burst pressure approx 1850 psi
- 100% Leak Tested
- Working pressure 200 psi
- No Sweat Installation
- Lifetime Warrantee
- Temperature rating -40 to 120 degrees F
- Bright annealed

COMPLIANCES/LISTINGS:

- * ICC-ES PMG
- * ICC Listed, Tested & Certified
- * UPC, IPC, IMC, IRC (USA)
- * Low Lead Compliant California H & S Code 116875
- * ASME A112.18.6/CSA B125.6-2009 Compliant
- * NSF-61 (ICC-ES PMG Certified to ANSI/NSF section 9)

<u>Model #</u>	<u>Description</u>	<u>Length</u>
SWCN134x18	1” N FIP x ¾” FIP	18”
SWCN-1141x12	114 N FIP x 1” FIP	12”
SWCN-1141x15	114 N FIP x 1” FIP	15”
SWCN-1141x18	114 N FIP x 1” FIP	18”
SWCN-1141x24	114 N FIP x 1” FIP	24”



<u>Product Submittal</u>	
Job Name:	_____
Date:	_____
Model#	Quantity: _____

Architect/Contractor: _____	

