



**Corrugated Stainless Steel Flexible
 Water Heater/Softener Connectors
 Specification Sheet**

SPECIFICATION:

Furnish and install Corrugated Stainless Steel Water Heater &/or Softener Connectors

DESIGN FEATURES: Mega-flow SUPER Water-flex™

- 304 Series Stainless Steel
- 3/4" ID SS Flex with 3/4" FIP x 7/8" Copper Sweat
- Sweat Not available in braided type
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chrome plated brass nut
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- High Temp EPDM Washer
Chlorine and Chloramine Resistant
- Resists work hardening
- Working pressure 200 psi
- Burst pressure approx 1850 psi
- 100% Leak Tested
- Sweat Installation
- Lifetime Warrantee
- Temperature rating -40 to 220 degrees F
- Bright annealed

COMPLIANCES/LISTINGS:

- * ICC-ES PMG
- * ICC Listed, Tested & Certified
- * UPC, IPC, IMC, IRC (USA)
- * Low Lead Compliant California H & S Code 116875
- * ASME A112.18.6/CSA B125.6-2009 Compliant
- * NSF-61 (ICC-ES PMG Certified to ANSI/NSF section 9)

<u>Model #</u>	<u>Description</u>	<u>Length</u>
H3404		
SWTxFEMx15	3/4" FIP x 7/8" Copper Swt	15"
SWTxFEMx18	3/4" FIP x 7/8" Copper Swt	18"
SWTxFEMx24	3/4" FIP x 7/8" Copper Swt	24"



<u>Product Submittal</u>	
<u>Job Name:</u>	_____
<u>Date:</u>	_____
<u>Model#</u>	<u>Quantity:</u>
_____	_____
<u>Architect/Contractor:</u>	

