



**Corrugated Stainless Steel Flexible  
 Toilet Connectors  
 Specification Sheet**

**SPECIFICATION:**

Furnish and install Corrugated Stainless Steel Toilet Connector

**COMPLIANCES/LISTINGS:**

- \* ICC-ES PMG
- \* ICC Listed, Tested & Certified
- \* UPC, IPC, IMC, IRC (USA)
- \* Low Lead Compliant California H & S Code 116875
- \* ASME A112.18.6/CSA B125.6-2009 Compliant
- \* NSF-61 (ICC-ES PMG Certified to ANSI/NSF section 9)

**DESIGN FEATURES: Mega-flow SUPER Water-flex™**

- 304 Series Stainless Steel
- Easy Installation
- Installs without tools
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chromed **brass** nuts
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- High Temp EPDM Washer
- Chlorine and Chloramine Resistant
- Resists work hardening
- Burst pressure approx 1850 psi
- 100% Leak Tested
- Working pressure 200 psi
- No Sweat Installation
- Lifetime Warrantee
- Temperature rating -40 to 220 degrees F
- Bright annealed

<u>Model #</u>	<u>Description</u>	<u>Length</u>
T-07	7/8" Ballcock x 1/2" FIP	9", 12"
T-06	7/8" Ballcock x 3/8" Comp	9", 12"



Product Submittal

Job Name: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Model# \_\_\_\_\_ Quantity: \_\_\_\_\_  
 \_\_\_\_\_  
 Architect/Contractor: \_\_\_\_\_  
 \_\_\_\_\_

